

neofeu)

PERSONAL PROTECTION EQUIPMENT FOR FALL PROTECTION

ASC'O®

Guided type fall
arrester on flexible
anchorage line



Fall
Protection
Only



+ INFOS

ASC'O®

GUIDED TYPE FALL ARRESTER ON FLEXIBLE ANCHORAGE LINE

ref.: NSD19.P

Main body in anodized aluminum

MAX
140 KG



Tested for use
up to 140kg



R ≥ 0.5

Tested for horizontal
use (ED\GE) (1)

Use on rope Ø 11mm

CERTIFICATION (1) (2)

EN 353-2 : 2002

RfU 11.062

EN 12841-A : 2006

RfU 11.075

(1) (2) According to applicable configurations.



EASY SAFE UNIQUE

Unique patented
opening system



Designed and
assembled in France

Aluminum twist lock
connector

Locking
button for stopping
position of ASC'O®
on rope



SAFETY IN ALL CIRCUMSTANCES

ASC'O® is a mobile fall arrester in aluminum to use on **TWIST 11®** rope to secure your works at height.

In normal use, the device slides hands free on the rope up and down automatically.

Should a fall occur or in case of unexpected descent, the **ASC'O®** locks instantly and secures the user.

With its **unique patented opening system**, **ASC'O®** mobile fall arrester associates comfort of use and maximum safety.

It can be locked on the rope to allow the user to remain hands free at any level of the rope.

USES

Fall arrest use according to standard **EN 353-2**.



Fall arrest use **EN 353-2** and horizontal **RfU 11.075**.



Rope access according to standard **EN 12841**.



ACCESSORIES AND FLEXIBLE ANCHORAGE LINE

NEX.35

Extension lanyard for **ASC'O®** guided type fall arrester.

- Allows the user to work at a distance from the rope
- Fitted with an automatic aluminum connector

EN 353-2 RfU 11.062

EN 12841-A

KG
140 KG



ABS'O®40

Shock absorber for **ASC'O®** guided type fall arrester.

- Tested in horizontal use
- Allows the user to work at a distance from the rope
- Fitted with an automatic aluminum connector

EN 353-2 RfU 11.062 - 11.075

EN 12841-A

KG
140 KG



TWIST 11®

Flexible anchorage line
Semi-static rope Ø 11mm

- Very low static elongation, soft and easy to handle
- Excellent grip

NTWIST

EN 1891-A

NTWISTC

EN 353-2

In use with ASC'O®




(3) Recommended connector for use with ASC'O®.

EASY AND SAFE TO SET UP



With its innovative opening system, **ASC'O®** is very user friendly. Easy to open and to set up with no possible mistake. Once locked, it is not possible to open it by chance.

Simple, fast and safe, it takes only a few seconds to insert **ASC'O®** on its associated rope (**TWIST 11®**).



+33 (0)4 78 48 75 33



neofeu@neofeu.com



neofeu.com

8 Allée de l'Industrie - Z.I R.Bloch - Chassagny
F69700 Beauvallon



by PMS GROUP
FABRICANT FRANÇAIS